
## MULTIMAX

by **ESWINDOWS** 

Residential Windows and Doors







## Features

- Single source warranty: in-house aluminum and glass processing
- Laminated glass by industry leader Tecnoglass
- Heat strengthened and annealed glass in clear and gray as standard
- Superior energy efficiency with Solarban 70 Low-E glass
- Powder paint in white and bronze
- Stainless steel corrosion-resistant hardware for coastal areas as standard

#### WINDOWS

ES-MX1000 Single Hung Window

ES-MX1500 Fixed Window

ES-MX2000 Horizontal Roller / Sliding Window

## DOORS

ES-MX3000 French Door / Swing Door

ES-MX4000 Sliding Glass Door

#### SINGLE HUNG WINDOW

## **ES-MX1000**

The ES-MX1000 is a single hung window that can be adapted to any architectural design. The system follows strict construction specifications and architectural standards of safety and durability. This window system can be implemented in residential and commercial construction projects.

#### **System Description**

- Maximum size: 53 1/8" x 74 1/4"

- Minimum size: 19" x 26"- Frame depth: 3 1/16"- Sill height: 2 13/16"

- Flange frame available

- Design for 5/16" annealed and heat strengthened glass

- LMI and SMI- Configuration: OX

- Water infiltration: 12 psf.

- Design load:

• +80/-90 psf. (LMI)

• +80/-120 psf. (SMI)

- Laminated glass:

• 1/8" ANN + 0.09 PVB + 1/8" ANN

• 1/8" HS + 0.09 PVB + 1/8" HS

#### **Features**

- Low-E Solarban 70 available
- Screen option available
- Block and tackle and ultra-lift balance options
- White and bronze powder aluminum finishes
- Sweep lock and vent latch handles available
- Heavy-duty meeting rail available







#### **FIXED WINDOW**

## **ES-MX1500**

ES-MX1500 is an impact-rated fixed window available in a variety of shapes allowing a wide range of architectural applications. This window is used to bring light to places with difficult accessibility.

#### **System Description**

- Maximum size: 36" x 120"
- Minimum size: 15" x 15"
- Frame depth: 2 5/16"
- Flange frame available
- Design for 5/16" annealed glass and 7/16" heat strengthened glass
- LMI and SMI
- Water infiltration: 15 psf.
- Design load:
- +70/-80 psf. (LMI)
- +100/-140 psf. (SMI)
- Laminated glass:
- 1/8" ANN + 0.09 PVB + 1/8" ANN
- 3/16" HS + 0.09 PVB + 3/16" HS

#### **Features**

- Low-E Solarban 70 available
- White and bronze powder aluminum finishes
- PVB laminated glass with coating options available
- Architectural shapes





#### **HORIZONTAL ROLLER / SLIDING WINDOW**

## **ES-MX2000**

ES-MX2000 is an impact-rated horizontal sliding window. This product ensures an easy and smooth opening allowing maximum ventilation. ES-MX2000 can be used on a wide variety of architectural applications.

#### **System Description**

Maximum size: 111" x 63"
Minimum size: 20" x 20"
Frame depth: 2 15/16"
Sill height: 3 5/16"

- Flange and flush frame available

- Design for 5/16" annealed and heat strengthened glass

- LMI and SMI

- Configurations: OX, XO, XOX - Water infiltration: 12 psf.

- Design load:

+80/-90 psf. (LMI)+82/-108 psf. (SMI)

- Laminated glass:

1/8" ANN + 0.09 PVB + 1/8" ANN
1/8" HS + 0.09 PVB + 1/8" HS

#### **Features**

- Low-E Solarban 70 available

- Screen option available

- White and bronze powder aluminum finishes

- PVB laminated glass with coating options available

- Sweep lock and vent latch handles available

- Heavy duty meeting rail available





# The Power of **Quality**



## DOORS

#### FRENCH DOOR / SWING DOOR

## **ES-MX3000**

ES-MX3000 is an impact-rated french door designed with the highest technical standards in safety and durability. This door system can be used in a wide range of residential and commercial applications.

#### **System Description**

- Maximum size:
- Single leaf: 40" x 96"
- Double leaf: 76" x 96"
- Minimum size:
- Single leaf: 20" x 40"
- Double leaf: 40" x 70"
- Frame depth: 4"
- Design for 5/16" heat strengthened glass
- Prepped handle bores options only
- Water infiltration: 13.5 psf. (single) 15 psf. (double)
- Design load: +80/-70 psf.
- Laminated glass:
- 1/8" HS + 0.09 PVB + 1/8" HS

#### **Features**

- Low-E Solarban 70 available
- White and bronze powder aluminum finishes
- PVB laminated glass with coating options available







#### **SLIDING GLASS DOOR**

## **ES-MX4000**

ES-MX4000 is an impact-rated sliding glass door system designed with the highest technical standards in safety and durability. This system is very versatile and can be implemented in interiors or exteriors for a wide range of residential and commercial projects.

#### **System Description**

- Maximum size: 48" x 108" panels - Minimum size: 25" x 71" panels

- Frame depth: 4 9/16" - Sill height: 2 5/8"

- 2 track, and up to 4 panel configuration with screens

- Configurations: OX, XO, OXO, OXXO

- Water infiltration: 12 psf.

Design load:+70/-80 psf.

• +80/-103 psf. (OX and XO only)

- Laminated glass:

• 1/8" HS + 0.09 PVB + 1/8" HS

#### **Features**

- Low-E Solarban 70 available

- Screen option available

- White and bronze powder aluminum finishes

- PVB laminated glass with coating options available

- Reinforcement available





## Colors & Finishes



**POWDER BRONZE** 



**POWDER WHITE** 



ES-MX4000

## Accessories

Every Multimax window and door benefits from a combination of premium materials, cutting-edge production technology and the talent of an experienced team. All of these result in precise stylish designs that will endure over time.



Vent Latch
ES-MX1000
ES-MX2000



Sweep Lock
ES-MX1000
ES-MX2000



Horizontal Roller ES-MX2000



Involute ES-MX4000



Roller ES-MX4000



## QUALITY MEETS AFFORDABILITY

